

KM08S NAMUR SERIES

ARTICLE PROPERTIES

SENSOR TYPE	Inductive sensor	CONNECTION TYPES (<i>see table</i>)
SIZE	M8x1	• cable PVC, 0.18 mm ² , 2 m**
RATED OPERATING DISTANCE	<i>see table</i>	
NUMBER OF CONDUCTORS	2-wire (<i>see table</i>)	** other cable lengths are available on request

MECHANICAL DATA

MOUNTING (mounting nuts included in delivery)	flush/non-flush (<i>see table</i>)
HOUSING	threaded cylindrical
MATERIAL HOUSING	stainless steel
MATERIAL SENSING SURFACE	PBT
TIGHTENING TORQUE LOCKING	2 Nm
STANDARD TEST	FE360
ATTENUATION COEFFICIENT	St37 = 1, V2A = 0.7, Al = 0.3

ELECTRICAL DATA

OPERATING VOLTAGE	DC: 7.7 ... 9 V DC
RATED OPERATING CURRENT	2-wire: ≤ 1 mA (trigger) ≥ 2.2 mA (not trigger)
SWITCHING FREQUENCY	<i>see table</i>
SWITCHING OUTPUT	<i>see table</i>
FUNCTION INDICATOR	yellow LED
HYSTERESIS	3 ... 15 %
TEMPERATURE DRIFT	±10 %
SHORT-CIRCUIT PROTECTION	yes
OVERLOAD RESISTANCE	yes
REVERSE POLARITY PROTECTION	yes

ENVIRONMENTAL CONDITIONS

PROTECTION CLASS	IP67	VIBRATION RESISTANCE (EN 60068-2-27)	55 Hz, 1 mm
AMBIENT TEMPERATURE	-25 ... 70 °C	SHOCK RESISTANCE (EN 60068-2-6)	30g/11 ms

STANDARDS AND DIRECTIVES

LOW-VOLTAGE SWITCHGEAR AND CONTROLGEAR	DIN EN IEC 60947-5-2:2021-04
---	------------------------------

APPROVALS



KM08S NAMUR SERIES

DC 2-WIRE OUTPUT CABLE

Article number	Mounting	Rated operating distance Sn	Switching output (wiring diagram)	Switching frequency	Dimensions
Fi1.5-KM08S-NE	flush	1.5 mm	NAMUR NC (WD14)	1000 Hz	see Fig. 1
Ni2-KM08S-NE	non-flush	2 mm	NAMUR NC (WD14)	800 Hz	see Fig. 2

DIMENSIONS

Fig. 1 Inductive sensor with cable (flush)






Fig. 1 Inductive sensor with cable (non-flush)




KM08S NAMUR SERIES

WIRING DIAGRAMS (Note: 1 / 2 / 3 / 4 connector and terminals pin number Bn / Bu / Wh / Bk cable color)


WD1 DC 2-wire NO




WD2 DC 2-wire NC




WD3 AC 2-wire NO




WD4 AC 2-wire NC




WD5 AC / DC 2-wire NO




WD6 AC / DC 2-wire NC




WD7 DC 3-wire PNP NO




WD8 DC 3-wire NPN NO




WD9 DC 3-wire PNP NC




WD10 DC 3-wire NPN NC



WD11 DC 4-wire PNP NO + NC



WD12 DC 4-wire NPN NO + NC




The information contained in this data sheet was compiled with the greatest possible care. Liability for correctness, completeness and topicality is limited to gross negligence.


KM08S NAMUR SERIES

WIRING DIAGRAMS (Note: 1 / 2 / 3 / 4 connector and terminals pin number Bn / Bu / Wh / Bk cable color)

WD13 AC/DC 4-wire NO+NC



WD14 NAMUR 2-wire NC



WD15 DC 4-wire 0-10V+0-20mA

