Product Description:

- Cylindrical circular hole installation,rectangular screw installation method optional.
- Suitable for applications such as automotive parts,packaging, logistics transportation,metal processing,etc.

Product features:

- Compact size ang appearance
- Visible red light

Polarized retro-reflective

Type	Distance	Beam	Output	Connection	Wiring
OSQ18-RPVP6 *M[1)]	3.5m	Red	PNP	Cable	Fig.1
OSQ18-RPVP6Q	3.5m	Red	PNP	M12 Connetor	Fig.2
OSQ18-RPVN6 *M[1)]	3.5m	Red	NPN	Cable	Fig.3
OSQ18-RPVN6Q	3.5m	Red	NPN	M12 Connetor	Fig.4

Note 1): * M refers to the cable length in meters. If there is no * M in the model, the default cable length is 2 meters.

TECHNICAL SPECIFICATION

OPERATING VOLTAGE	10...30 V DC
RIPPLE VOLTAGE	≤10%
LIGHT SOURCE TYPE	Red LED
OUTPUT CHARACTERISTIC	PNP/NPN
LOAD CURRENT	≤200mA
SWITCHING FREQUENCY	800Hz
ADJUSTMENT OF SENSITIVITY	Knob adjustment

AMBIENT TEMPERATURE OPERATION	-25°C...+55°C
AMBIENT TEMPERATURE STORAGE	-40°C...+70°C
CIRCUIT PROTECTION	Short-circuit protection, reverse polarity protection, over-load protection
PROTECTION DEGREE	IP67
HOUSING MATERIAL	PBT+ABS
CONNECTING TYPE	*m TPU cable /M12 connector

OSQ18 SERIES PHOTOELECTRIC SENSOR

DIMENSIONS

M12 Connetor



Cable



INDICATORS

A	Potentiometer	
B	output indicator	Yellow
C	stable indicator	Green



ELECTRICAL CONNECTION



Fig.1



Fig.2



Fig.3



Fig.4



○ =Light on
● =Dark on

We reserve the right to make technical technical alterations without prior notice . | EN&CN | Creation date:21.11.25 | UM_SP_OSQ18-RP_V1.0_EN&CN

产品说明:

- 圆柱形圆孔安装，矩形螺丝安装方式可选。
- 适用汽车零部件，包装，物流输送，金属加工等应用。

偏振镜反式

产品特点:

- 小巧的尺寸外形
- 可见红光

型号	检测距离	光源	输出方式	连接方式	接线图
OSQ18-RPVP6 *M [1)]	3.5m	红光	PNP	线缆	图1
OSQ18-RPVP6Q	3.5m	红光	PNP	M12 连接器	图2
OSQ18-RPVN6 *M [1)]	3.5m	红光	NPN	线缆	图3
OSQ18-RPVN6Q	3.5m	红光	NPN	M12 连接器	图4

注1)：*M表示线缆长度，单位米，型号中无*M默认线缆长度为2米。

技术参数

工作电压	10...30 V DC
纹波电压	≤10%
光源	红光
输出特性	PNP/NPN
负载电流	≤200mA
开关频率	800Hz
灵敏度调节	旋钮调节

工作温度	-25°C...+55°C
环境温度	-40°C...+70°C
保护电路	短路保护 反极性保护 输出过载保护
防护等级	IP67
外壳	PBT+ABS
连接方式	*m TPU 线缆 /M12连接器

OSQ18系列光电传感器

外形尺寸

M12 连接器



线缆



操作指示

A	电位器调节	
B	开关动作指示灯	黄色LED
C	电源稳态指示灯	绿色LED



接线图



图1



图2



图3



图4